

## RF Power Amplifier

## RF2000 2200 - 50

This solid state power amplifier is designed for reliable, trouble-free service. It operates in a class A and includes RF protection circuits, cooling installations and a 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

### Features :

- \* 60 Watts saturated output power
- \* 47 dB minimum gain
- \* Electronic Attenuator in option
- \* RF coupler and meter or RS232 in option
- \* Temperature protection

### Applications :

- \* Microwaves links
- \* Tests Bench
- \* Fields Test
- \* Instrumentations

### Specifications

Characteristics	Data	Units
Frequency range	2000 - 2200	MHz
RF output power CW		
Typ.	60	W
Min	50	W
Class	A	
Power gain min	50	dB
Flatness	+/- 2 dB	dB
Input power for rated output power	0	dBm
Max. input power	13	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2 : 1	
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch		
Protection circuits	Load VSWR, overtemperature	
Harmonics typ.	-20	dBc
Spurious typ.	-60	dBc
Modulation capability	100	%
Noise Figure typ.	10	dB
Intercept point 3rd Order min.	> 60	dBm
RF connectors	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % , 47-63 Hz	V
Dimensions (W x L x H)	4 U 19" Rack 482 x 460 x 176	mm

All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice